

# EMERGENCY LIGHTING AND ORIENTATION SYSTEMS

ARSEL 



## STARLITE EMERGENCY LIGHTING FIXTURE

- Surface mounting, metal sheet case
- 3mm acrylic diffuser
- DALI compatible models

- For door-top applications, suitable for standards, for decorative emergency exit routing.
- 8w T5 and LED lamp models
- There are 2 fluorescent lamps with fluorescent lamps and continuous lighting. One of the lamps is on line voltage and the other is power failure.
- The mains supply voltage is standard 220 volts AC 50 Hz.
- Charging time for first use is 24 hours.
- It can withstand fluctuations up to 285 volts at mains voltage.
- Switches to emergency lighting mode under 150 volts, charging over 185 volts
- It is manufactured according to TS 8710 EN60598-2-22 standard in the framework of ISO 9001-2000 quality management system.

### USAGE AREAS

- Offices
- Grocery stores
- Corridors
- Restaurants and bars
- Universities, Student dormitories, Schools and colleges

### LAMP OPTIONS

- G5 socket T5 8w fluorescent bulb, 6500°K
- White light LED bulb, 6500°K

### BODY STRUCTURE

- Body - Powder white painted sheet metal chassis
- With label panel - 3 mm acrylic panel, application of latex on white foil
- BATTERY - Nickel-cadmium in all models

### OPTIONS

- Continuous and emergency models
- 1-2-3 hour emergency backup times
- DALI lighting control system compatible models



## STARLITE EMERGENCY LIGHTING FIXTURE

MODEL CODE	LIGHTING STYLE	MOUNTING STYLE	LAMP	LIGHT FACE	DURATION (minute)	DIMENSIONS (W-L-H)mm	WEIGHT	IP CLASS	ISOLATION CLASS	OPERATION TEMP	POWER CONSUMPTION	OPERATING VOLTAGE
AE-01111	Emergency Light	Wall Mount	8 wat	Single Face	Emergency 60 m.	70x350x145mm	1,70kg	40	I	-16/+45°	3w	220-240
AE-01112	Emergency Light	Wall Mount	8 wat	Single Face	Emergency 120 m.	70x350x145mm	1,85kg	40	I	-16/+45°	3w	220-240
AE-01113	Emergency Light	Wall Mount	8 wat	Single Face	Emergency 180 m.	70x350x145mm	1,90kg	40	I	-16/+45°	3w	220-240
AE-01211	Combined m.	Wall Mount	2x8 wat	Single Face	Emergency 60 m.	70x350x145mm	2,00kg	40	I	-16/+45°	11w	220-240
AE-01212	Combined m.	Wall Mount	2x8 wat	Single Face	Emergency 120 m.	70x350x145mm	2,15kg	40	I	-16/+45°	11w	220-240
AE-01213	Combined m.	Wall Mount	2x8 wat	Single Face	Emergency 180 m.	70x350x145mm	2,20kg	40	I	-16/+45°	11w	220-240
AE-01113-L	Emergency Light	Wall Mount	1000lm LED	Single Face	Emergency 180 m.	70x350x145mm	1,90kg	40	I	-16/+45°	1w	220-240
AE-01213-L	Maintained	Wall Mount	1000lm LED	Single Face	Emergency 180 m.	70x350x145mm	1,90kg	40	I	-16/+45°	5,5w	220-240
AE-01010	Mains Light	Wall Mount	1000lm LED	Single Face	—	70x350x145mm	1,55kg	40	I	-16/+45°	4,7w	220-240

## STARLITE EMERGENCY LIGHTING FIXTURE (DALI compatible)

MODEL CODE	LIGHTING STYLE	MOUNTING STYLE	LAMP	LIGHT FACE	DURATION (minute)	DIMENSIONS (W-L-H)mm	WEIGHT	IP CLASS	ISOLATION CLASS	OPERATION TEMP	POWER CONSUMPTION	OPERATING VOLTAGE
AE-01111-L-DALI	Emergency Light	Wall Mount	500lm LED	Single Face	Emergency 60 m.	70x350x145mm	0,80kg	40	I	-16/+45°	1,2w	220-240
AE-01112-L-DALI	Emergency Light	Wall Mount	500lm LED	Single Face	Emergency 120 m.	70x350x145mm	0,85kg	40	I	-16/+45°	1,2w	220-240
AE-01113-L-DALI	Emergency Light	Wall Mount	500lm LED	Single Face	Emergency 180 m.	70x350x145mm	0,90kg	40	I	-16/+45°	1,2w	220-240
AE-01211-L-DALI	Maintained	Wall Mount	500lm LED	Single Face	Emergency 60 m.	70x350x145mm	0,80kg	40	I	-16/+45°	4,5w	220-240
AE-01212-L-DALI	Maintained	Wall Mount	500lm LED	Single Face	Emergency 120 m.	70x350x145mm	0,85kg	40	I	-16/+45°	4,5w	220-240
AE-01213-L-DALI	Maintained	Wall Mount	500lm LED	Single Face	Emergency 180 m.	70x350x145mm	0,90kg	40	I	-16/+45°	4,5w	220-240

## DIMENSIONS

